having run clear through the Section both ways and ascertained the center of the two division lines by measurement.

Henry Tettrick and George S. Tettrick Chain Bearers

John B. Kelshaw County Surveyor G. C. Ca.

October the 31st 1838. Then Proceeded to Survey 6 Acres and ninety four hundredths of an acre in the S.E. Corner of the N.W.¼ of the aforesaid Section 35 for Andrew Ferguson Begmning at the S.E. corner of Said ¼ at the before mentioned stone Then N. 5° 12' W. 5.39 Chains and made a corner at a stone Then S. 88° W. 8.60 Chains to a stone at a Maple 18 Ins. dia. S. 88° W. 22 Links and B. Oak 4 Ins. dia. S 57¾ W. 38¾ Links Then S. 14° W. 4.85 Chains to a stone in a Road at a W. Oak 24 Ins. dia. N. 88½ W. 156 Links Then S. 83¼ W. 11.88 Chains to a Stone at a Walnut 30 Ins. dia. S. 21° W. 51 Links then South 1.15 Chains and made a Corner on the East and West line running through the Center of Section and 17.97 Chains East of the West Quarter stake at a stone at a Walnut 30 Ins. dia. N. 16° W. 66 Links and W. Oak 18 Ins dia. S. 67° W. 59¾ Links Then N. 84° 12' E. 22.10 Chains to the place of Beginning.

Andrew Fergnson and Charles L. Rader Chain Bearers.

John B. Kelshaw County Surveyor G. C.

No. 46.

October the 31st 1838. Then Surveyed for Samuel Fergnson a lot in the S.E.¼ of Section 35 In T. 7. N. R. 3 W. Containing 1 Acre and 18 hundredths of an acre Beginning at a Stone corner No. 1. Bearing from the Center of Section aforesaid S. 62¼ E. 8.71 Chains then N. 68¾ E. 3.05 Chains to a stone Corner No. 2. Then S. 27° E. 4.32¾ Chains to a stone Corner No. 3. Then S. 66¾ W. 2.27¾ Chains to a stone Corner No. 4. Then N. 36½ W. 4.53¼ Chains to the place of Beginning. This lot was sold

by Isaac Storm Senior to Samuel Ferguson.

Andrew Ferguson and Wm. Dugger Chain Bearers.

John B. Kelshaw County Surveyor G. C.

No 47

October the 31st and November the 1st 1838 Then Surveyed for William Dugger one lot in Section 35. T. 7. N. R. 3. W. partly on the S. W. corner of N. E.¼ and partly on the N. W. Corner of S. E.¼ Beginning at a Stone corner No. 1. Bearing from the Stone Corner at the Center of Section N. 1½ W. 88 Links lacking about 1. Inch. then N. 86½ E. 116 feet and 2 Inches to a stone Corner No. 2. Then S. 4 2/12 E. 193 feet and 6. Inches to a stone corner No. 3. Then S 87° W. 112 feet to a stone corner No. 4. at an Apple tree 10 Inches dia. N. 14¾ W. Links Then N. 6° W. 193 feet 6 Inches to the place of Beginning by Containing by Computation 81 Rods and 17+ hundredths of a Rod. Andrew Ferguson and Edmund Bingham Chain Bearers.

John B Kelshaw County Surveyor G. C. Ca.

No 48.

November the 13th 14th and 15th and 16th 1838. Then Surveyed for John Stanley and John Hubble in T. 8. N. R. 6. W. Section 17. For Stanly the W.½ of the N. E.¼ and the N. E.¼ of N. W.¼ of Said Section and for Hubble the E.½ of the S. W. ¼ and the S. W.¼ of S. W. ¼ and S. E.¼ of N. W. ¼ and N. W.¼ of S. E¼ of Said section. Beginning at the S. W. corner of Said Section. Then N. 6° W. 38 Chains to Saggoon Creek and squared west 50 Links and took the Angle which was 18¼ Calculated the distance across Said Creek 1.51½ Chains then Continued Same course 34.92½ Chains to the Section line Then went to the S. E. Corner of Section then N. 6½ W. 40.28¾ Chains to the Quarter Stake then Same Course continued 33.45 Chains.